

Exhibit 1

How Computers Work

Millennium Edition

Ron White

Illustrated by Timothy Edward Downs and Stephen Adams

que®

A Division of Macmillan Computer Publishing, USA
201 W. 103rd Street
Indianapolis, IN 46290

How Computers Work, Millennium Edition
Copyright© 1999 by Que® Corporation.
First printing: September 1999

Publisher	Greg Wiegand
Executive Editor	Angela Wethington
Acquisitions Editor	Angelina Ward
Development Editor	Sarah Robbins
Managing Editor	Thomas F. Hayes
Project Editor	Leah Kirkpatrick
Copy Editor	Leah Kirkpatrick
Technical Illustrators	Timothy Edward Downs and Stephen Adams
Book Designers	Anne Jones and Dan Armstrong
Page Layout	Trina Wurst
Proofreader	Tricia Sterling
Indexer	Christine Nelsen

All other product names and services identified throughout this book are trademarks or registered trademarks of their respective companies. They are used throughout this book in editorial fashion only and not for the benefit of such companies. No such uses, or the use of any trade name, is intended to convey endorsement or other affiliation with the book.

No part of this publication may be reproduced in any form, or stored in a database or retrieval system, or transmitted or distributed in any form by any means, electronic, mechanical photocopying, recording, or otherwise, without the prior written permission of Que, except as permitted by the Copyright Act of 1976.

THE INFORMATION AND MATERIAL CONTAINED IN THIS BOOK ARE PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTY CONCERNING THE ACCURACY, ADEQUACY, OR COMPLETENESS OF SUCH INFORMATION OR MATERIAL OR THE RESULTS TO BE OBTAINED FROM USING SUCH INFORMATION OR MATERIAL. NEITHER QUE NOR THE AUTHOR SHALL BE RESPONSIBLE FOR ANY CLAIMS ATTRIBUTABLE TO ERRORS, OMISSIONS, OR OTHER INACCURACIES IN THE INFORMATION OR MATERIAL CONTAINED IN THIS BOOK, AND IN NO EVENT SHALL QUE OR THE AUTHOR BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF SUCH INFORMATION OR MATERIAL. SO THERE.

Manufactured in the United States of America

Library of Congress Catalog No.: 98-85290

ISBN: 0-7897-2112-0

This book is sold as is, without warranty of any kind, either express or implied, respecting the contents of this book, including but not limited to implied warranties for the book's quality, performance, merchantability, or fitness for any particular purpose. Neither Que Corporation nor its dealers or distributors shall be liable to the purchaser or any other person or entity with respect to any liability, loss, or damage caused or alleged to have been caused directly or indirectly by this book.

00 6 5

Interpretation of the printing code: the rightmost double-digit number is the year of the book's printing; the rightmost single-digit number, the number of the book's printing. For example, a printing code of 99-1 shows that the first printing of the book occurred in 1999.

All terms mentioned in this book that are known to be trademarks or service marks have been appropriately capitalized. Que cannot attest to the accuracy of this information. Use of a term in this book should not be regarded as affecting the validity of any trademark or service mark. Que is a trademark of Macmillan Computer Publishing.

This book was written on a Hewlett-Packard 7370V, a Gateway Solo 2100, and an IBM Aptiva Pentium II using WordPerfect, Microsoft Word, Professional Capture System, Paint Shop Pro, Notes 4.5, Windows Explorer, Netscape Navigator, and a BitSURFR ISDN connection. Author's color proofs produced with Hewlett-Packard OfficeJet Pro 1150C. It was produced on a Power Macintosh G3, with the following applications: Adobe Illustrator, QuarkXPress, Microsoft Word, Adobe Photoshop, Aldus FreeHand, and Collage Plus.

This book was produced digitally by Macmillan Computer Publishing and manufactured using computer-to-plate technology (a filmless process) by GAC, Indianapolis, Indiana.

How a Super-VGA Display Works

2 The DAC compares the digital values sent by the PC to a *look-up table* that contains the matching voltage levels for the three primary colors needed to create the color of a single pixel. In a normal VGA adapter, the table contains values for 262,144 possible colors, of which 256 values can be stored in the VGA adapter's memory at one time. Super-VGA adapters have enough memory to store 16 bits of information for each pixel (16,000 colors, called *high color*) or 24 bits a pixel (16,777,216 shades—or *true color*).

VOLTAGES			
RED	GREEN	BLUE	
5	2.5	1	
5	2.5	2	
5	2.5	3	
5	2.5	4	
5	2.5	5	

3 The adapter sends signals to three electron guns located at the back of the monitor's *cathode-ray tube (CRT)*. Through the vacuum inside the CRT, each electron gun shoots out a stream of electrons, one stream for each of the three primary colors. The intensity of each stream is controlled by the signals from the adapter.

4 The adapter also sends signals to a mechanism in the neck of the CRT that focuses and aims the electron beam. The mechanism, a *magnetic deflection yoke*, uses electromagnetic fields to steer the path of the electron streams. The signals sent to the yoke help determine the monitor's *resolution*—the number of pixels displayed horizontally and vertically—and the monitor's *refresh rate*, which is how frequently the screen's image is redrawn.


1 Digital signals from the operating environment or application software go to the *super video graphics array (SVGA)* adapter. The adapter runs the signals through a circuit called a *digital-to-analog converter (DAC)*. Usually the DAC circuit is contained within one specialized chip, which actually contains three DACs—one for each of the primary colors used in a display: red, blue, and green.

the beam
called a
to keep
with the
screen.
how clo
the hole
creates
shadow
Imports
CRT use
Trinitron


5 The beams pass through holes in a metal plate called a *shadow mask*. The purpose of the mask is to keep the electron beams precisely aligned with their targets on the inside of the CRT's screen. The CRT's *dot pitch* is the measurement of how close the holes are to each other; the closer the holes, the smaller the dot pitch. This, in turn, creates a sharper image. The holes in most shadow masks are arranged in triangles, with the important exception of those of the Sony Trinitron CRT used by many monitor manufacturers. The Trinitron's holes are arranged as parallel slots.

6 The electrons strike the phosphors coating the inside of the screen. Phosphors are materials that glow when they are struck by electrons. Three different phosphor materials are used—one each for red, blue, and green. The stronger the electron beam that hits a phosphor, the more light the phosphor emits. If each red, green, and blue dot in an arrangement is struck by equally intense electron beams, the result is a dot of white light. To create different colors, the intensity of each of the three beams is varied. After a beam leaves a phosphor dot, the phosphor continues to glow briefly, a condition called *persistence*. For an image to remain stable, the phosphors must be reactivated by repeated scans of the electron beams before the persistence fades away.

7 After the beams make one horizontal sweep across the screen, the electron streams are turned off as the magnetic yoke refocuses the path of the beams back to the left edge of the screen at a point just below the previous *scan line*. This process is called *raster scanning*.



8 The magnetic deflection yoke continually changes the angles at which the electron beams are bent so that they sweep across the entire screen surface from the upper-left corner of the screen to the lower-right corner. A complete sweep of the screen is called a *field*. Upon completing a field, the beams return to the upper-left corner to begin a new field. The screen is normally *redrawn*, or *refreshed*, about 60 times a second.



9 Some display adapters scan only every other line with each field, a process called *interlacing*. Interlacing allows the adapter to create higher resolutions—that is, to scan more lines—with less expensive components. But the fading of the phosphors between each pass can be noticeable, causing the screen to flicker.